

DEADFRONT TERMINAL BLOCKS

MARATHON SPECIAL PRODUCTS

1100, 1103P, 1200, 0987RZ, 885 AND 985GP SERIES

1100, 1103P and 1200 Series

Electrical Specifications

- 65 amps (1100 Series)
- 70 amps (1103P and 1200 Series)
- 600 volts
- Base wire range #6 - 18 AWG CU
- Base, phenolic, 150°C (UL RTI)
- Wire Range:
 - 1103P - (1) #4 - 14 AWG CU & (1-2) #10 - 14 AWG CU
 - 1200 - (1) #4 - 18 AWG CU
- Pressure spring, copper (11xxS only)

Standards

- UL recognized file no. XCFR2.E62806
- CSA certified file no. LR19766
- CE (Component IEC 60947-7-1)
- RoHS compliant

Ordering Codes

1100 Series

11XX
11XXS

1103P Series

1103P

1200 Series

12XX
12XXS

S = Copper Pressure
Spring

1100, 1103P and 1200 Series - Stocklist

1102	1106	1108	1103P
1102S	1106S	1108S	1202
1104	1107	1112	1204
1104S	1107S	1112S	1206

Standard Pack Quantity: 10pcs

Datasheets available from Global Supply Services
simonp@global-supply-services.com

0987 Series

Electrical Specifications

- 50 amps
- 600 volts
- Base, plastic, 125°C (UL RTI)
- IP20 touchproof protection
- .475" centerline spacing
- Screws, steel, nickel plated
- Wire Range:
 - (1) #8 - #24 sol/str
 - (2) 12 str
 - (2) 14 str
 - (1) 12 str and (1) 14 str

Standards

- UL recognized file no. XCFR2.E62806
- CE (Component IEC 60947-7-1)
- CSA certified file no. LR19766
- RoHS compliant

0987 RZ Series - Stocklist

0987 RZ TC 02	0987 RZ TC 05	0987 RZ TC 08	0987 RZ TC 11
0987 RZ TC 03	0987 RZ TC 06	0987 RZ TC 09	0987 RZ TC 12
0987 RZ TC 04	0987 RZ TC 07	0987 RZ TC 10	

Standard Pack Quantity: 10pcs

Datasheets available from Global Supply Services
simonp@global-supply-services.com

885 Series

Specifications

- 85 amps
- 600 volts
- Base, thermoplastic, 130°C (UL RTI)
- .432" centreline spacing
- Accommodates conductor sizes #4 AWG - #18 AWG
- Numbered terminal positions
- Screws: steel, tin plated

Standards

- UL recognized file no. XCFR2.E62806

885 Series - Stocklist

885 RZ 01	885 RZ 04	885 RZ 07	885 RZ 10
885 RZ 02	885 RZ 05	885 RZ 08	885 RZ 11
885 RZ 03	885 RZ 06	885 RZ 09	885 RZ 12

Standard Pack Quantity: 10pcs

Datasheets available from Global Supply Services
simonp@global-supply-services.com

985GP Series

Electrical Specifications

- 85 amps
 - 600 volts
 - Base, phenolic, 150°C (UL RTI)
 - Screws, steel, tin plated
 - Connector, aluminum, tin plated
 - .625" centreline spacing
- Wire Range:
 - (1) #4 - #18 AWG
 - (1-2) #8 AWG
 - (1-4) #10-12 AWG
 - (1-6) #14-16 AWG
 - (1-8) #18

Standards

- UL recognized file no. XCFR2.E62806
- CSA certified file no. LR19766
- CE (Component IEC 60947-7-1)
- RoHS compliant

985GP Series - Stocklist

985 GP 02
985 GP 03
985 GP 04

985 GP 05
985 GP 06
985 GP 07

985 GP 08
985 GP 09
985 GP 10

985 GP 11
985 GP 12

Standard Pack Quantity: 10pcs

Datasheets available from Global Supply Services
simonp@global-supply-services.com